

Panasonic

Home Security Video Intercom VL-SF70

Wired Video Intercom System

- 7-inch-wide Monitor
- 3 Monitors Connectable
- Picture Recording
- Electric Lock Release Support
- Night Vision
- Intercom



3-Monitor Connectable

A maximum of three monitors* can be connected. By installing them in the living room and other rooms where you spend the most time, you can answer the visitor immediately.

*Optional monitors are sold separately.



7-inch Wide Screen

The main monitor has a 7-inch wide screen that clearly shows each visitor's face. It offers easy viewing at wide angles both vertical and horizontal.

Electric Lock Release Support

The electronic lock can be operated from the monitor. The door lock can be easily and quickly released even from the second floor of the house if an additional monitor* is connected.



7-inch-wide Screen
3 Monitors Connectable
Picture Recording

[SEE ALL SPECS](#)

Panasonic Video Intercom System Line-up



VL-VF580CX

Door Station



VL-MF70CX

Monitor

[COPY URL](#)

Wired Video Intercom VL-SF70

Model composition		VL-VF580 x1,
Model composition		VL-MF70 x1
Optional Accessories	Door Station	VL-VF580CX (1 included in VL-SF70)
	Monitor	VL-MF70CX (1 included in VL-SF70)
Maximum	Door Station	UP to 2 (1 included in VL-SF70)

Connectable Units	Monitor	UP to 3 (1 included in VL-SF70)
Connectable Devices	Electric Lock Release Support	UP to 2 (User supplied)
	PBX	No
Convenience	Picture Recording	Up to 50 events / 50 images
	Picture Recording	(1-shot recording)
	Night Vision	White coloured LED lights
	Voice Changer	No
	Intercom call	Between monitors
	Intercom call	* Multiple Monitors are required
Monitor	Power source	AC adaptor (PNLV245CX), 24 V DC, 0.5A
	Power consumption	Standby: Approx. 1.3 W
	Power consumption	During operation: Approx. 10 W
	Dimensions (H x W x D)	Approx. 135 x 201 x 25.5 mm
	Mass (weight)	Approx. 465 g

	Operating environment	Ambient temperature: Approx. 0 °C to +40 °C Relative humidity (non-condensing): from 45 % up to 90 %
	Display	Approx. 7 inches wide colour display
	Talking method	Hands-free
	Installation method	Wall mount (mounting bracket supplied)
	External material	Flame retardant ABS resin
Door Station	Power source	Supplied by the Monitor
	Dimensions (H x W x D)	Approx. 143 x 101 x 35 mm
	Mass (weight)	Approx. 265 g
	Operating environment	Ambient temperature: Approx. -10 °C to +50 °C Relative humidity (non-condensing): up to 90 %
	Viewing angle	Horizontally: Approx. 51° Vertically: Approx. 38°
	Installation method	Wall mount (Mounting base attached)
	Minimum illuminance required	1 lx
	Minimum illuminance	(within approx. 50cm from the camera lens)

	required	
	Lighting method	White coloured LED lights
	IP rating (INGRESS PROTECTION)	IP44-rated water and dust resistant
	External material	Flame retardant ABS resin